



ZEBRA SOL PRIMER FOR KERB MARKING

Zebra sol primer enamel based its look to surfaces painted with matt finish. High quality, alkali resistant white primer with high obliteration. Formulated with excellent penetration and adhesion for subsequent top coat. Primer paint gives your finish paint job a smoother finish than if you did not use a primer at all because of paint grips better and it will last much longer.

Technical Data	
Finish	Matt
Volume solids	approx. 20 %
Recommended DFT/Coat	35 -50 micron
Theoretical Coverage	8 - 10 sq. m/ltr dependent on surface texture and porosity.
Drying time	Surface Dry : 1 - 2 hrs
Flash Point	35°C

Advantages

- Excellent Adhesion on Kerb
- Hard durable surface with good over coating abilities.
- Good binding power.
- Fast drying.
- Lead free guarantee, chrome and other toxic metal ingredients.

Method of Use:

- Clean the Kerb surface thoroughly removing all dust, oil grease and paint.
- Ensure the Kerb surface is completely dry and free from moisture.
- Cold and humid conditions require a longer drying time. Such conditions should be avoided.
- Temperature at the time of application should not be above 60°C and below 10°C.
- Humidity should not be above 85%.

Method of Application:

- To be applied by Brush/Machine.
- If thinning is required solvent may be used sparingly.
- Clean all equipment immediately after use with Solvent. Dried paint on equipment could be removed by ketonic solvents.

Mixing:

- Thorough mixing should be done before application.

Colours: White

Packing: 20 Ltr

AUTOMARK INDUSTRIES (INDIA) PVT. LTD.



Corporate Office :-

2nd & 3rd Floor, 2, Lotus Plaza, Opposite VCA Stadium,
Gate No. 2, Civil Lines, Nagpur - 440001.(M.S)
India.

PH# +91 0712 6603687/680/6615768 email :- info@automark-india.com

Fax3 +91 0712 6603679

Site : www.automar-india.com

Plant : At post Bothali village, Behind Islamic Madarasa. Wardha Road, Nagpur - 441108

CIN - U24290MH2002PTC135673